

# Evolution — EV 700 P BT

Pastry and bakery



## Technical data

Gross volume	630 lt
Working temperature	-22+40 °C
Humidity range	55%-95%
Motor type	Plug-in
Refrigerant	R290
Refrigeration power	568 W (-25°C / +45°C)
Absorption	1079 W
Voltage/Frequency	230V/1~/50Hz

## Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors
Refrigerant charge	115 gr
Evaporator	Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity
Defrost	Automatic by hot gas for a shorter cycle and less thermal shocks
Condensate evaporation	Automatic by electric heater

## Construction details

---

Product dimensions WxDxH	702x882x2080
Packaging dimensions WxDxH	770x910x2190
Gross weight	143 Kg
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	1 Self-closing door with 105° door stop. Right hinged, reversible on-site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)

## Functions

---

Control panel	7" touch screen graphic display
Open door alarm	Visual and acoustic
Functions	Automatic retarder proving cycles (composed by stopping, holding, reactivation, proving and storage phases) and manual storage and proving cycles (with temperature and humidity management), HACCP alarms
Languages	Italian, English, French, German, Spanish, Portuguese, traditional Chinese and simplified Chinese
Connection	As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification

## Accessories

---

Lighting	As standard
Lock	As standard
Nebulizer	As standard (water connection required)
No. included accessories	20 - Pair of runners for tray EN 600x400 mm (Mod. 700)

## Versions

---

Versions	Power supply frequency 60Hz
----------	-----------------------------